

Model	KIP45	KIP45E	KIP60	KIP60E	KIP80	KIP80E	KIP90E
Output kW	4.5	4.5	6	6	8	8	9
Sauna room min. m ³	3	3	5	5	7	7	8
Sauna room max. m ³	6	6	8	8	12	12	14
Sauna room height min. cm	190	190	190	190	190	190	190
Stone capacity max. kg	25	25	25	25	25	25	25
Dimensions width mm	410	410	410	410	410	410	410
Dimensions height mm	600	600	600	600	600	600	600
Dimensions depth mm	280	280	280	280	280	280	280
Weight kg	16	16	16	16	16	16	16
Supply voltage 3-phase	400V3N	400V3N	400V3N	400V3N	400V3N	400V3N	400V3N
Connecting cable mm ²	5x1,5	5x1,5	5x1,5	5x1,5	5x2,5	5x2,5	5x2,5
Fuse A	3x10	3x10	3x10	3x10	3x16	3x16	3x16
Supply voltage 1-phase	230V1N	230V1N	230V1N	230V1N			
Connecting cable mm ²	3x6	3x6	3x6	3x6			
Fuse A	1x20	1x20	1x25	1x25			
Control unit		C90, C150		C90, C150		C90, C150	C90, C150
Safety distance A to wall mm	35	35	50	50	100	100	120
Safety distance B to front lower platform mm	20	20	30	30	30	30	40
Safety distance C to upper platform mm	35	100	50	120	80	150	150
Safety distance to ceiling mm	1100	1100	1100	1100	1100	1100	1100
Safety distance to floor mm	150	150	150	150	150	150	150

